

# ST518

## Heavy Series | All Position

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application specific tread compound resists cutting and chipping.



Durable all-position tires for mixed service use.

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5531116*	10.00R20	146/143K	H/16	7.50	7.00	6,610	5,800	120	41.5	11.0	12.5	20	19.5	502	68
5531120*	11.00R20	150/147K	H/16	8.00	7.50	7,390	6,780	120	42.8	11.7	13.2	21	19.9	488	68
5531155	12R22.5	150/147K	H/16	9.00	8.25	7,390	6,780	120	42.8	12.0	13.5	21	20.0	488	68

\* Includes tube and flap

# ST508

## Heavy Series | All Position

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application specific tread compound resists cutting and chipping.



Durable all-position tires for mixed service use.

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5531023*	12.00R20	154/151K	J/18	8.50	8.00	8,270	7,610	120	44.1	12.1	14.2	21	20.5	474	68
5531032*	11.00R22	150/146K	H/16	8.00	7.50	7,830	7,160	120	44.7	11.7	13.0	20	21.1	462	68
5531035*	11.00R24	154/151K	H/16	8.00	7.50	8,270	7,610	120	46.9	11.5	-	20	21.8	276	68

\* Includes tube and flap