

# ST518

## Heavy Series | All Position

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application specific tread compound resists cutting and chipping.



Durable all-position tires for mixed service use.

| Product Code | Tire Size | Service Desc. | Load Range / Ply | Pref Rim Width (inch) | Min Rim Width (inch) | Single Max Load (lbs) | Dual Max Load (lbs) | I.P. (psi) | Overall Diameter (inch) | Section Width (inch) | Min Dual Spacing (inch) | Tread Depth (X/32") | Static Loaded Radius (inch) | Revs Per Mile | Max Speed (mph) |
|--------------|-----------|---------------|------------------|-----------------------|----------------------|-----------------------|---------------------|------------|-------------------------|----------------------|-------------------------|---------------------|-----------------------------|---------------|-----------------|
| 5531116*     | 10.00R20  | 146/143K      | H/16             | 7.50                  | 7.00                 | 6,610                 | 5,800               | 120        | 41.5                    | 11.0                 | 12.5                    | 20                  | 19.5                        | 502           | 68              |
| 5531120*     | 11.00R20  | 150/147K      | H/16             | 8.00                  | 7.50                 | 7,390                 | 6,780               | 120        | 42.8                    | 11.7                 | 13.2                    | 21                  | 19.9                        | 488           | 68              |
| 5531155      | 12R22.5   | 150/147K      | H/16             | 9.00                  | 8.25                 | 7,390                 | 6,780               | 120        | 42.8                    | 12.0                 | 13.5                    | 21                  | 20.0                        | 488           | 68              |

\* Includes tube and flap

# ST508

## Heavy Series | All Position

- Sumitomo four steel belt casing construction resists punctures, increases vehicle stability and contributes to more retread cycles.
- Application specific tread compound resists cutting and chipping.



Durable all-position tires for mixed service use.

| Product Code | Tire Size | Service Desc. | Load Range / Ply | Pref Rim Width (inch) | Min Rim Width (inch) | Single Max Load (lbs) | Dual Max Load (lbs) | I.P. (psi) | Overall Diameter (inch) | Section Width (inch) | Min Dual Spacing (inch) | Tread Depth (X/32") | Static Loaded Radius (inch) | Revs Per Mile | Max Speed (mph) |
|--------------|-----------|---------------|------------------|-----------------------|----------------------|-----------------------|---------------------|------------|-------------------------|----------------------|-------------------------|---------------------|-----------------------------|---------------|-----------------|
| 5531023*     | 12.00R20  | 154/151K      | J/18             | 8.50                  | 8.00                 | 8,270                 | 7,610               | 120        | 44.1                    | 12.1                 | 14.2                    | 21                  | 20.5                        | 474           | 68              |
| 5531032*     | 11.00R22  | 150/146K      | H/16             | 8.00                  | 7.50                 | 7,830                 | 7,160               | 120        | 44.7                    | 11.7                 | 13.0                    | 20                  | 21.1                        | 462           | 68              |
| 5531035*     | 11.00R24  | 154/151K      | H/16             | 8.00                  | 7.50                 | 8,270                 | 7,610               | 120        | 46.9                    | 11.5                 | -                       | 20                  | 21.8                        | 276           | 68              |

\* Includes tube and flap