


ST709SE

Regional Series | Steer

- Beefy 20/32" tread depth applied to a wide, flat casing for much longer life in high scuff applications.
- Chevron block center ribs with lateral sipes effectively cut water on wet roads for enhanced traction and safety.
- Thick curbing ribs help shield casing from sidewall damage.
- Stone ejectors protect the casing from damage in the base of the tread groove.
- An innovative design helps control irregular wear during on-highway use.
- Built with SmartWay Verified Technology.



The ST709SE is a regional steer tire that's durable enough when there's serious work to be done, but versatile enough to display on-highway manners.

ST709SE Featuring SmartWay Verified Technology

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5532952	11R22.5	146/143L	H/16	8.25	7.50	6,610	6,005	120	41.5	11.1	12.5	20	19.4	500	75
5532959	11R24.5	149/146L	H/16	8.25	7.50	7,160	6,610	120	43.5	11.1	12.5	20	20.4	477	75
5532975	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	40.2	11.3	13.2	20	18.8	517	75
5532978	285/75R24.5	144/141L	G/14	8.25	7.50	6,175	5,675	110	41.6	10.6	12.5	20	19.5	500	75

This company manufactures:

- EPA SmartWay verified technologies
- Verified equipment for SmartWay Certified Tractors - and /or
- Verified equipment for SmartWay Certified Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about...

SmartWay
www.epa.gov/smartway