

ST710SE

Premium Series | Trailer

- Sumitomo four steel belt casing construction resists punctures, increases trailer stability and contributes to more retread cycles.
- Shoulder grooves control migration of irregular wear.
- A wide footprint enhances vehicle stability and delivers long mileage.
- Pyramid shaped ribs put more rubber on the road as the tire wears.
- Stone ejectors protect the casing from damage in the base of the groove.



The SMARTWAY-Verified ST710SE merges the advantages of an advanced concept low-skid tread pattern with the long-term durability of a premium Sumitomo casing. Its high quality construction yields years of service. It wears long and smooth when new and is designed for multiple retread cycles.

ST710SE Featuring SmartWay Verified Technology

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5532651	11R22.5	144/142L	G/14	8.25	7.50	6,175	5,840	105	41.0	11.2	12.5	12	18.7	507	75
5532658	11R24.5	146/143L	G/14	8.25	7.50	6,610	6,005	105	43.0	11.1	12.5	12	19.8	483	75
5532675	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	39.8	11.3	13.2	12	18.3	522	75
5532678	285/75R24.5	144/141L	G/14	8.25	7.50	6,175	5,675	110	41.1	10.5	12.5	12	19.0	506	75

This company manufactures:

- EPA SmartWay verified technologies
- Verified equipment for SmartWay Certified Tractors - and /or
- Verified equipment for SmartWay Certified Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about...
SmartWay
www.epa.gov/smartway