

ST908

Value Series | Open Shoulder Drive

- A continuous center rib delivers long life and highway stability, while shoulder lugs bite for excellent traction on soft surfaces.
- 26/32" tread depth promotes long life and year round service.
- Four steel belt casing construction resists punctures, increases vehicle stability, and contributes to more retread cycles.



The ST908 open shoulder drive tire has an excellent reputation among fleets.

Product Code	Tire Size	Service Desc.	Load Range / Ply	Pref Rim Width (inch)	Min Rim Width (inch)	Single Max Load (lbs)	Dual Max Load (lbs)	I.P. (psi)	Overall Diameter (inch)	Section Width (inch)	Min Dual Spacing (inch)	Tread Depth (X/32")	Static Loaded Radius (inch)	Revs Per Mile	Max Speed (mph)
5531217*	10.00R20	146/143K	H/16	7.50	7.00	6,610	6,005	120	41.8	10.9	12.5	26	19.5	498	68
5531252	11R22.5	146/144L	H/16	8.25	7.50	6,610	6,005	120	41.9	10.9	12.6	26	19.6	495	75
5531255	12R22.5	150/147L	H/16	9.00	8.25	7,390	6,780	120	43.1	11.8	13.5	27	20.0	486	75
5531259	11R24.5	149/146L	H/16	8.25	7.50	7,160	6,610	120	43.9	10.9	12.6	26	20.7	470	75
5531263	315/80R22.5	154/151M	J/18	9.00	9.00	8,270	7,610	120	42.8	12.3	13.8	25	19.8	486	81
5531275	295/75R22.5	144/141L	G/14	9.00	8.25	6,175	5,675	110	40.7	10.7	13.2	26	19.0	512	75
5531287	255/70R22.5	140/137M	H/16	7.50	6.75	5,510	5,070	120	36.9	9.9	11.3	25	17.2	578	81
5531278	285/75R24.5	144/141L	G/14	8.25	7.50	6,175	5,675	110	42.0	10.6	12.5	26	19.7	494	75

* Includes tube and flap

